



Page: 1 of 5

Infosafe No™ 3CHKC Issue Date: October 2019 RE-ISSUED by ABS

Product Name: SAF FIXATIVE

Classified as hazardous

CHEMCALL (24 hours): 1800 127 406 (Australia) / +64-4-917-9888 (International)

1. Identification

GHS Product

SAF FIXATIVE

Identifier

ASAF Product Code

AUSTRALIAN BIOSTAIN Pty Ltd Company Name

Address 24 - 28 Stratton Drive.

> Traralgon, Victoria, Australia, 3844 www.australianbiostain.com.au

Telephone/Fax

Number

Tel: (03) 5176 2855

Emergency phone

number

Recommended use of the chemical and

restrictions on use Other Information

Laboratory reagent.

Australian Biostain Pty Ltd does not warrant that this product is suitable for any use or purpose. The user must ascertain the suitability of the product before use or application intended purpose. Preliminary testing of the product before use or application is recommended. Any reliance or purported reliance upon Australian Biostain Pty Ltd with respect to any skill or judgement or advice in relation to the suitability of this product of any purpose is disclaimed. Except to the extent prohibited at law, any condition implied by any statute as to the merchantable quality of this product or fitness for any purpose is hereby excluded. This product is not sold by description. Where the provisions of Part V, Division 2 of the Trade Practices Act apply, the liability of Australian Biostain Pty Ltd is limited to the replacement of supply of equivalent goods or payment of the cost of replacing the goods or acquiring equivalent goods.

2. Hazard Identification

GHS classification

substance/mixture

of the

Acute Toxicity - Oral: Category 4 Sensitization - Skin: Category 1 Skin Corrosion/Irritation: Category 2

Eve Damage/Irritation: Category 1 Acute Toxicity - Inhalation: Category 4 Carcinogenicity: Category 1B Acute Toxicity - Dermal: Category 4

Signal Word (s)

DANGER

Hazard Statement

H302 Harmful if swallowed.

(s)

H317 May cause an allergic skin reaction.

H315 Causes skin irritation. H318 Causes serious eye damage.

H332 Harmful if inhaled.

H350 May cause cancer.

H312 Harmful in contact with skin.

Pictogram (s)

Health hazard, Corrosion, Exclamation mark







Precautionary statement -

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray. Prevention

P264 Wash thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

Precautionary statement -Response

P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P330 Rinse mouth.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.



infosafe CS: 1.7.2

Page: 2 of 5

Infosafe No™ 3CHKC Issue Date: October 2019 RE-ISSUED by ABS

Product Name: **SAF FIXATIVE**

Classified as hazardous

P362 Take off contaminated clothing and wash before reuse.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician. P308+P313 IF exposed or concerned: Get medical advice/attention.

Precautionary

statement - Storage

Precautionary statement -

P501 Dispose of contents/container to anapproved waste disposal plant.

3. Composition/information on ingredients

Chemical Liquid

Characterization

Information on

Stabilised with methanol.

P405 Store locked up.

Composition Ingredients

Disposal

Name CAS **Proportion Hazard Symbol Risk Phrase** Formaldehyde 50-00-0 4 % Acetic acid 64-19-7 2 % Methanol 67-56-1 1 % Sodium acetate anhydrous 127-09-3 0.9 % Lutensol AO-109 64425-86-1 0.8 % Water to make a total of 100% 7732-18-5

4. First-aid measures

Inhalation If inhaled, remove from contaminated area to fresh air immediately. Apply artificial respiration if not

breathing. If breathing is difficult, give oxygen. Immediately obtain medical aid if cough or other

symptoms appear.

Rinse mouth thoroughly with water immediately, repeat until all traces of product have been removed. Ingestion

Give water to drink. DO NOT INDUCE VOMITING. Seek medical advice if symptoms persist.

Immediately remove contaminated clothing and wash affected area with water for at least 15 minutes. Skin

Ensure contaminated clothing is washed before re-use. Seek medical advice /attention depending on the

severity. Immediately irrigate with copious quantity of water for at least 15 minutes. Eyelids to be held open. In all

Eye contact cases of eye contamination it is a sensible precaution to seek medical advice.

First Aid Facilities Maintain eyewash fountain and safety shower in work area.

Advice to Doctor Treat symptomatically based on judgement of doctor and individual reactions of the patient.

Other Information For advice, contact a Poisons Information Centre (Phone eg Australia 13 1126; New Zealand 0800 764

766) or a doctor.

5. Fire-fighting measures

Hazards from Combustion **Products**

May liberate toxic fumes in fire including formic acid, methanol, carbon monoxide and carbon dioxide.

Small fire: Use foam, dry chemical, CO2 or water spray. **Specific Methods** Large fire: Use foam, fog or water spray. Do not use water jets.

If safe to do so, move undamaged containers from fire area. Cool containers with flooding quantities of

water until well after fire is out. Avoid getting water inside containers. Alcohol resistant foam is preferred however fine water spray can be used.

Precautions in

Wear SCBA, fully-encapsulating, gas-tight suit and structural firefighting uniform when handling leaking connection with Fire or damaged containers and equipment. SCBA and chemical splash suits will offer limited protection for

brief exposure provided there is no risk of ignition.

Accidental release measures

Evacuate the area of all non-essential personnel. Avoid inhalation, contact with skin, eyes and clothing. Personal

Precautions

Personal Protection Wear protective clothing specified for normal operations (see Section 8)



infosafe CS: 1.7.2

Page: 3 of 5

Infosafe No™ 3CHKC Issue Date: October 2019 RE-ISSUED by ABS

Product Name: SAF FIXATIVE

Classified as hazardous

Clean-up Methods -**Small Spillages**

Absorb or contain liquid with sand, earth or spill control material. Shovel up using non sparking tools and place in a labelled, sealable container for subsequent safe disposal. Put leaking containers in a labelled drum or overdrum.

Large Spillages

Clean-up Methods - Seek expert advice on handling and disposal.

7. Handling and storage

Handling

Precautions for Safe Avoid generation of vapours/aerosols. Do not breathe vapour. Avoid contact with eyes, skin and clothing. Avoid prolonged or repeated exposure. Work under hood.

Avoid exposure - obtain special instructions before use.

Conditions for safe storage, including

Store in cool place and out of direct sunlight. Store away from sources of heat or ignition. Store in well ventilated area. Store away from oxidising agents, acids, alkalis, metal salts and foodstuff. Keep containers closed at all times - check regularly for leaks.

STEL

TWA

incompatabilities

8. Exposure co	ntrols/personal protection
Occupational	Name

exposure limit values						
		<u>mg/m3</u>	ppm	<u>mg/m3</u>	ppm	Footnote
	Formaldehyde	2.5	2	1.2	1	
	Acetic acid	37	15	25	10	

Other Exposure
Information

200 Methanol 328 250 262 These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

The STEL (Short Term Exposure Limit) is an exposure value that should not be exceeded for more than 15 minutes and should not be repeated for more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The exposure value at the TWA is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. Note: Absorption through skin may be a significant route of exposure for methyl alcohol.

Note: Sensitiser (for formaldehyde). Known to act as a sensitiser. - Safe Work Australia. Sensitiser notice: Some substances can cause a specific immune response in some people. Such substances are called sensitisers and the development of a specific immune response is termed 'sensitisation'. Exposure to a sensitiser, once sensitisation has occurred, may manifest itself as a skin rash or inflammation or as an asthmatic condition, and in some individuals this reaction can be extremely

Appropriate

In industrial situations maintain the concentrations values below the TWA. This may be achieved by engineering controls process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. These methods should be used in preference to personal protective equipment.

Respiratory **Protection**

Where ventilation is not adequate, respiratory protection may be required. Avoid breathing vapours or mists. Select and use respirators in accordance with AS 1716 - Respiratory Protective Devices and be selected in accordance with AS 1715 - Selection, Use and Maintenance of Respiratory Protective Devices. When mists or vapours exceed the exposure standards then the use of the following is recommended: Approved respirator with organic vapour and dust/mist filters. Filter capacity and respirator type depends on exposure levels.

Eye Protection Hand Protection

The use of a face shield, chemical goggles or safety glasses with side shield protection as appropriate. Must comply with Australian Standards AS 1337 and be selected and used in accordance with AS 1336. Hand protection should comply with AS 2161, Occupational protective gloves - Selection, use and maintenance. Recommendation: Excellent: Vinyl gloves. Good: NR latex, nitrile and neoprene. Avoid skin contact when removing gloves from hands, do not touch the gloves outer surface. Dispose of gloves as hazardous waste.

Personal Protective

Personal protective equipment should not solely be relied upon to control risk and should only be used when all other reasonably practicable control measures do not eliminate or sufficiently minimise risk. Guidance in selecting personal protective equipment can be obtained from Australian, Australian/New Zealand or other approved standards.

Equipment

Footwear

Safety boots in industrial situations is advisory, foot protection should comply with AS 2210, Occupational protective footwear - Guide to selection, care and use.





Page: 4 of 5

Infosafe No™ 3CHKC Issue Date : October 2019 RE-ISSUED by ABS

Product Name: SAF FIXATIVE

Classified as hazardous

Body Protection Clean impervious clothing should be worn, preferably with an apron for extra protection. Clothing for

protection against chemicals should comply with AS 3765 Clothing for Protection Against Hazardous

Chemicals.

Hygiene Measures Always wash hands before smoking, eating or using the toilet. Wash contaminated clothing and other

protective equipment before storing or re-using.

9. Physical and chemical properties

Form Liquid

Odour Faintly Acetic and sharp.

Solubility in Water Completely miscible.

Flammability Combustible liquid.

Relative density 1.080 g/cm3

10. Stability and reactivity

Chemical Stability Stable under normal use conditions.

Conditions to Avoid Open flames, heat, hot surfaces, sparks and other ignition sources. **Incompatible** Strong oxidizing agents, strong acids, strong bases, alkali metals.

Materials

Hazardous Formic acid, methanol, carbon monoxide and carbon dioxide.

Decomposition Products

11. Toxicological Information

Acute Toxicity - Oral LD50 (rat): >200 mg/kg (Formaldehyde).

Ingestion Harmful if swallowed. Ingestion may cause irritation of the mouth, throat and stomach resulting in

nausea. In extreme cases swallowing can result in vomiting, diarrhoea, abdominal pain, convulsions, chemical burns, loss of consciousness, collapse and possible death. Risk of perforation in the

oesophagus and stomach. Systemic effects: narcosis and blindness.

Inhalation Harmful if inhaled. Inhalation may lead to the formation of oedemas in the respiratory tract. Vapour is

irritating to mucous membranes and the respiratory tract. Inhalation can result in headache, dizziness

and possible nausea.

Skin May cause on allergic skin reaction. Repeated or prolonged skin contact may lead to allergic contact

dermatitis. A skin sensitiser.

Eye May be an irritant to the eye.

Respiratory sensitisation

Not classified based on available information.

Skin Sensitisation Not classified based on available information.

Formaldehyde: Known to act as a sensitiser. Not classified based on available information.

Germ cell mutagenicity Carcinogenicity

H350 May cause cancer.

Formaldehyde [50-00-0] is evaluated in the IARC Monographs (Vol. 88; in preparation) as Group 1:

Carcinogenic to humans.

For addition information see IARC publication:

http://monographs.iarc.fr/ENG/Monographs/vol100F/mono100F-29.pdf Not classified based on available information.

Reproductive Toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration Hazard Not classified based on available information.

Chronic Effects Repeated or prolonged skin contact may cause chronic dermatitis. Harmful: possible risk of irreversible

effects through inhalation, in contact with skin and if swallowed.

Mutagenicity Not classified based on available information.

12. Ecological information

Print Date: 6/12/2019 CS: 1.7.2





Page: 5 of 5

Infosafe No™ 3CHKC Issue Date: October 2019 RE-ISSUED by ABS

SAF FIXATIVE Product Name:

Classified as hazardous

Ecological

The following statements refer to individual components of the preparation:

Information

Abiotic degradation: Rapid degradation. (air, formaldehyde)

Persistence and degradability

Biologic degradation: Biodegradation: 97.4 % /5 d (Formaldehyde). Readily biodegradable.

COD: 1.06 g/g (Formaldehyde); TOD: 1.068 g/g (Formaldehyde)

Bioaccumulative

Potential

No bioaccumulation is to be expected (log P(o/w < 1)).

Distribution: log p(o/w): 0.00 (Formaldehyde).

Biological Properties

Mobility

Toxic for aquatic organisms. Protoplasmatic toxin. Caustic even in diluted form. Disinfectant effect. Toxic

effect on fish and plankton. Sludge decomposition impaired or not possible even in diluted concentration. Endangers drinking-water supplies if allowed to enter soil and/or waters in large

Maximum permissible toxic concentration: Algeal toxicity: Sc.quadricauda IC5: 2.5 mg/l /8 d

Environmental Protection

Do not allow to enter waters, waste water, or soil!

Acute Toxicity - Fish LC50 (P.promelas): 24 mg/l /96 h (Formaldehyde);

LC50 (Br.rerio): 41 mg/l /96 h (Formaldehyde).

Acute Toxicity -

Daphnia magna EC50: ~2 mg/l /48 h (Formaldehyde).

Daphnia

Acute Toxicity -Algae

(Formaldehyde).

Acute Toxicity -Bacteria

Photobacterium phosphoreum EC50: 8.5 mg/l /30 min (Formaldehyde). Bacterial toxicity: M.aeruginosa EC5: 0.39 mg/l /8 d (Formaldehyde).

13. Disposal considerations

Disposal Considerations Whatever cannot be saved for recovery or recycling should be disposed of according to relevant local,

state and federal government regulations.

14. Transport information

Transport Information Not classified as a Dangerous Good according to the Australian Code for the Transport of Dangerous

Goods by Road and Rail.

15. Regulatory information

Regulatory Information Listed in the Australian Inventory of Chemical Substances (AICS).

Poisons Schedule

S6

16. Other Information

Literature References 'Standard for the Uniform Scheduling of Medicines and Poisons .', Commonwealth of Australia.

Lewis, Richard J. Sr. 'Hawley's Condensed Chemical Dictionary 13th. Ed.', Rev., John Wiley and Sons,

Inc., NY, 1997.

National Road Transport Commission, 'Australian Code for the Transport of Dangerous Goods by Road

and Rail 7th. Ed.', 2007.

Safe Work Australia, 'National Code of Practice fot the Preparation of Safety Data Sheets for Hazardous

Chemicals', 2011.

Standards Australia, 'SAA/SNZ HB 76:2010 Dangerous Goods - Initial Emergency Response Guide', Standards Australia/Standards New Zealand, 2010.

Safe Work Australia, 'Approved Criteria for Classifying Hazardous Substances [NOHSC:1008 (2004)]'.

Safe Work Australia, 'Hazardous Chemical Information System, 2005'.

Safe Work Australia, 'National Code of Practice for the Labelling of Safe Work Hazardous Substances (2011)'

Safe Work Australia, 'National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995) 3rd Edition]'.

...End Of MSDS...

© Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd. The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.